According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name:Bausch Arti-Spray® (colored blue, green, red)REF:BK 286, BK 287, BK 288Product group:Occlusion spraysVersion:005 / EN (English Translation of German SDS)

Revision date: 2024-05-29

### Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 **Product identifier**

Product form	Mixture
Trade name	Bausch Arti®-Spray BK 286, BK 287, BK 288
Product use	Universal color indicator to test the occlusal contacts and accurate fit of crowns and
	bridges.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

### 1.2.1 Relevant identified uses

Function or use category

Coating

# 1.2.2 Uses adviced against

Restrictions on use no intraoral application, for professional use only

### 1.3 Details of the supplier of the safety data sheet

Dr. Jean Bausch GmbH & Co. KG, Oskar-Schindler-Str.4, 50769 Köln Telefon +49 (0)221-70936-0, Telefax +49 (0)221-70936-66 info@bauschdental.de, http://bauschdental.de

E-mail address (competent person)	pb@bauschdental.de
Contact person for information	Peter Bausch (CEO)
National contact person	Peter Bausch (CEO)

### 1.3 Emergency telephone number

Peter Bausch (CEO) Telephone +49 (0)221-70936-20, Mobil +49 (0)172-2601451

# Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Aerosol, Category 1

H222;

H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

# Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

### 2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 Hazard pictograms



Signal word

Danger

# Hazard statements

H222 H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name: REF:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red) BK 286, BK 287, BK 288	
Product group: Version:	Occlusion sprays 005 / EN (English Translation of German SDS)	Revision date: 2024-05-29

Precautionary statements Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251 Storage	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### 2.3 Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1 %.

# Section 3: Composition/information on ingredients

### 3.1 Substances

The product is a mixture.

### 3.2 Mixtures

Chemical name	CAS- No EG- No Index- No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32-XXXX	50 - < 75	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	(Note C) (Note U)
Propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-XXXX	10 - < 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	(Note U)

Comments -

C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

U: (table 3.1): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16.

# Section 4: First aid measures

### 4.1 Description of first aid measures

First-aid measures general	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
First-aid measures after inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
First-aid measures after skin contact	Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Get medical advice/attention.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red)
REF:	BK 286, BK 287, BK 288
Product group:	Occlusion sprays
Version:	005 / EN (English Translation of German SDS)

Revision date: 2024-05-29

### 4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

# **Section 5: Firefighting measures**

### 5.1 Extinguishing media

Symptoms/effects

Suitable extinguishing media	Water spray. Dry chemical, CO2, dry sand, or alcohol-resistant foam.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2 Special hazards arising from the substance or mixture

Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.
Reactivity in case of firel	In the event of fire hazardous gases may occur.
5.3 Advice for firefighters	
Firefighting instructions	Move container from fire area if it can be done without risk. Use water spray or fog for cooling exposed containers.
Protection during firefighting	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Wear fire/flame resistant/retardant clothing.
Other information	Use standard firefighting procedures and consider the hazards of other involved materials.

# Section 6: Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures

General measures	Do not handle until all safety precautions have been read and understood. Eliminate every possible source of ignition.
6.1.1. For non-emergency personnel	
Emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/ leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
6.1.2. For emergency responders Protective equipment	Wear recommended personal protective equipment.
Emergency procedures	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the MSDS.

### 6.2 Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red)
REF:	BK 286, BK 287, BK 288
Product group:	Occlusion sprays
Version:	005 / EN (English Translation of German SDS)

Revision date: 2024-05-29

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Remove all sources of ignition. Keep away from combustible material. Stop the leak. Prevent entry into waterways, sewer, basements or confined areas.

Other information

### 6.4 Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

# Section 7: Handling and storage

# 7.1 Safe handling

Precautions for safe handling	Keep away from sources of ignition - No smoking. Do not pierce or burn, even
	after use. Use only outdoors or in a well-ventilated area. Ground/bond container
	and receiving equipment. Avoid prolonged exposure. Avoid contact with eyes.
	Observe good industrial hygiene practices. Do not eat, drink or smoke when
	using this product. Wear appropriate personal protective equipment. Keep only
	in original container. Avoid release to the environment.
	na ha dhadha ann ha canna dh litha a

### 7.2 Conditions for safe storage, including any incompatibilities

Storage conditions	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well- ventilated place. Keep container tightly closed. Keep away from ignition sources.
Storage class (LGK, TRGS 510)	LGK 2B – Aerosol dispensers and lighters

### 7.3 Specific end use(s)

Coating.

# Section 8: Exposure controls/personal protection

### 8.1 Control parameters

### 8.1.1 National occupational exposure and biological limit values

### Butane (106-97-8)

#### Germany - Occupational Exposure Limits (TRGS 900)

Local name	Butan
AGW (OEL TWA) [1]	2400 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	1000 ppm
AGW (OEL C)	9600 mg/m <sup>3</sup>
AGW (OEL C) [ppm]	4000 ppm
Remark	DFG
Regulatory reference	TRGS 900

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name: REF:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red) BK 286, BK 287, BK 288	
Product group: Version:	Occlusion sprays 005 / EN (English Translation of German SDS)	Revision date: 2024-05-29

#### Propane (74-98-6)

Germany - Occupational Exposure Limits (TRGS 900)		
Local name	Pro	
	40	

AGW (OEL TWA) [1]
AGW (OEL TWA) [2]
Überschreitungsfaktor d. Spitzenbegrenzung
Remark
Regulatory reference

Propan 1800 mg/m<sup>3</sup> 1000 ppm 4(II) DFG TRGS 900

#### Germany - Occupational Exposure Limits (Generic OEL data)

1800 mg/m<sup>3</sup> (8-Stunden); 7200 mg/m<sup>3</sup> (15-Minuten)

DFG-MAK Liste (empfohlene Arbeitsplatzgrenzwerte) Propan (CAS 74-98-6)

### 8.1.2 Recommended monitoring procedures

No additional information available.

# 8.1.3 Air contaminants formed

No additional information available.

### 8.1.4 DNEL and PNEC

No additional information available.

### 8.1.5 Control banding

No additional information available.

### 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### 8.2.2 Personal protection equipment

### Personal protective equipment

Wear recommended personal protective equipment.

### 8.2.2.1. Eye and face protection

### Eye protection

If skin or eye contact with the product is probable, protective glasses with side shield are recommended.

### 8.2.2.2. Skin protection

Skin and body protection

Wear suitable protective clothing.

### Hand protection

Wear appropriate protective gloves for prolonged or repeated skin contact.

### Other skin protection

### Materials for protective clothing

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

### 8.2.2.3. Respiratory protection

In case of inadequate ventilation wear respiratory protection.

# 8.2.2.4. Thermal hazard protection

Wear appropriate thermal protective clothing, when necessary.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red)	
REF:	BK 286, BK 287, BK 288	
Product group: Version:	Occlusion sprays 005 / EN (English Translation of German SDS)	Revision date: 2024-05-29

### 8.2.3. Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases.

### Other information

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# Section 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

s. I mornation on basic physical and chemical properties			
Physical state	Gas		
Appearance	Aerosol		
Colour	blue, green, red		
Odour	Characteristic		
Odour threshold	No data available.		
Melting point	-188 – -138 °C (1013 hPa)		
Freezing point	No data available.		
Boiling point	-42 – 0 °C (1013 hPA)		
Flammability (solid, gas)	Extremely flammable aerosol		
Explosive properties	May form explosive/flammable vapor/air mixtures during use.		
Explosive limits	No data available.		
Lower explosive limit (LEL)	1.5 vol %		
Upper explosive limit (UEL)	10.9 vol %		
Flash point	Aerosol/Not applicable.		
Auto-ignition temperature	365 – 470 °C		
Decomposition temperature	No data available.		
рН	Not applicable.		
Viscosity, kinematic	Not applicable.		
Solubility	Water: < 0.1 g/l (20 °C)		
Log Kow	No data available		
Vapour pressure	2200 - 8400 hPa (20°C)		
Vapour pressure at 50°C	No data available.		
Density	0.5 – 0.58 g/m³ (20°C)		
Relative density	Not applicable.		
Relative vapour density at 20°C	No data available.		
Relative density of saturated gas/air mixture	1.55 – 2.09		
Particle size	Not applicable.		
Particle size distribution	Not applicable.		
Particle shape	Not applicable.		
Particle aspect ratio	Not applicable.		
Particle aggregation state	Not applicable.		
Particle agglomeration state	Not applicable.		
Particle specific surface area	Not applicable.		
Particle dustiness	Not applicable.		
9.2 Other information			

### 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

% of flammable ingredients		Not applicable.
9.2.2	Other safety characteristics	
VOC (E	EU)	Not applicable.

# Section 10: Stability and reactivity

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name: REF:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red) BK 286, BK 287, BK 288	
Product group: Version:	Occlusion sprays 005 / EN (English Translation of German SDS)	Revision date: 2024-05-29

### 10.1 Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### **10.2** Chemical stability

Stable under normal conditions of use.

### 10.3 Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4 Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5 Incompatible materials

Strong oxidizers.

### 10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral)	Based on available data, the classification criteria are not met.
Acute toxicity (dermal)	Based on available data, the classification criteria are not met.
Acute toxicity (inhalation)	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Based on available data, the classification criteria are not met.
Respiratory or skin sensitization	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT- repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

Arti-Spray BK 286 287, 288, blue, green, red (Occlusion spray)	
Vaporizer	Aerosol

# 11.2 Information on other hazards

### 11.2.1. Endocrine disrupting properties

### 11.2.2. Other information

Potential adverse human effects and symptoms

Occupational exposure to the substance or mixture may cause adverse effects.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name: REF:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red) BK 286, BK 287, BK 288	
Product group: Version:	Occlusion sprays 005 / EN (English Translation of German SDS)	Revision date: 2024-05-29

# Section 12: Ecological information

# 12.1 Toxicity

Ecology – general	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Hazardous to the aquatic environment, short-term (acute)	Based on available data, the classification criteria are not met.	
Hazardous to the aquatic environment, long-term (chronic)	Based on available data, the classification criteria are not met.	
12.2 Persistence and degradability		
Butane (106-97-8)		
Persistence and degradability	Readily biodegradable.	

### Propane (74-98-6)

Persistence and degradability

Readily biodegradable.

# 12.3 Bioaccumulative potential

Butane (106-97-8)	
Log Pow	1.09 – 2.8 @ 20 °C, pH 7
Propane (74-98-6)	
Log Pow	1.09 – 2.8 @ 20 °C, pH 7
42.4 Mahility in Cail	

# 12.4 Mobility in Soil

No additional information available.

# 12.5 Results of PBT and vPvB assessment

### **Occlusion spray**

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

# 12.6 Endocrine disrupting properties

No additional information available.

### 12.7 Other adverse effects

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

# Section 13: Disposal considerations

### 13.1 Waste treatment methods

Regional legislation (waste)	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Waste treatment methods	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name: REF:	Bausch Arti-Sp BK 286, BK 28	ray <sup>®</sup> (colored blue, green, red) 7. BK 288	
Product group: Version:	Occlusion sprays 005 / EN (English Translation of German SDS)		Revision date: 2024-05-29
Product/Packaging disp	osal	Since emptied containers may retain proc	•

recommendations	after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
Additional information	Dispose in accordance with all applicable regulations.
European List of Waste (LoW) code	08 02 01 - waste coating powders 15 01 04 - metallic packaging

# Section 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number

UN-No. (ADR)	UN 1950
UN-No. (IMDG)	UN 1950
UN-No. (IATA)	UN 1950
UN-No. (ADN)	UN 1950
UN-No. (RID)	UN 1950

### 14.2. UN proper shipping name

DSOLS
DSOLS
ols, flammable
DSOLS
DSOLS

# 14.3. Transport hazard class(es)

# ADR

Transport hazard class(es) (ADR)	2.1
Danger labels (ADR)	2.1
IMDG	
Transport hazard class(es) (IMDG)	2.1
Danger labels (IMDG)	2.1
ΙΑΤΑ	
Transport hazard class(es) (IATA)	2.1
Danger labels (IATA)	2.1
ADN	
Transport hazard class(es) (ADN)	2.1
Danger labels (ADN)	2.1
RID	
Transport hazard class(es) (RID)	2.1
Danger labels (RID)	2.1

**Safety Data Sheet** According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name: REF: Product group: Version:	BK 286, BK 287, Occlusion sprays		Revision date: 2024-05-29
14.4. Packing group	)		
Packing group (ADR)		Not applicable.	
Packing group (IMDG)		Not applicable.	
Packing group (IATA)		Not applicable.	
Packing group (ADN)		Not applicable.	
Packing group (RID)		Not applicable.	
14.5. Environmental	l hazards		
Dangerous for the enviror	nment	No	
Marine pollutant		No	
Other information		No supplementary information available.	
14.6. Special precau	itions for user		
Overland transport			
Classification code (ADR)		5F	
Special provisions (ADR)		190, 327, 344, 625	
Limited quantities (ADR)		11	
Packing instructions (ADF	R)	P207	
Tunnel restriction code (A	DR)	D	
Transport by sea			
Special provisions (IMDG	)	63, 190, 277, 327, 344, 381, 959	
Packing instructions (IMD	G)	P207, LP200	
EmS-No. (Fire)		F-D	
EmS-No. (Spillage)		S-U	
Stowage category (IMDG)	)	None	
Air transport			
PCA Expected quantities	(IATA)	E0	
PCA Limited quantities (IA	ATA)	Y203	
PCA limited quantity max	net quantity (IATA)	30kgG	
PCA packing instructions	(IATA)	203	
PCA max net quantity (IA	TA)	75kg	
CAO packing instructions	(IATA)	203	
CAO max net quantity (IA	TA)	150kg	
Special provisions (IATA)		A145, A167, A802	
ERG code (IATA)		10L	
Inland waterway transpo	ort		
Classification code (ADN)		5F	
Special provisions (ADN)		190, 327, 344, 625	
Limited quantities (ADN)		1L	

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name: REF:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red) BK 286, BK 287, BK 288	
Product group: Version:	Occlusion sprays 005 / EN (English Translation of German SDS)	Revision date: 2024-05-29

### **Rail transport**

Special provisions (RID)	190, 327, 344, 625
Limited quantities (RID)	1L
Packing instructions (RID)	P207, LP200
Hazard information number (RID)	23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

# Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1 EU-Regulations

EU restriction list (REACH Annex XVII)	
Reference code	Α

Reference codeApplicable on40.Butane; Propane

Contains no substance on the REACH candidate list.

Contains no REACH Annex XIV substances.

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

VOC content	Not applicable.
Other information, restriction and prohibition regulations	Directive 94/33/EC on the protection of young people at work, as amended is applicable. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended is applicable. Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended.

P3a

# Directive 2012/18/EU (SEVESO III)

Seveso Additional information

# 15.1.2 National regulations

Germany

Employment restrictions	Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
	Observe restrictions according Act on the Protection of Working Mothers MuSchG).
	Observe restrictions according Prohibition of Chemicals Ordinance
	(ChemVerbotsV).
Water hazard class (WGK)	WGK nwg, Non-hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance	Listed in the 12. BlmSchV (Annex I) under: 1.2.3.1
(12. BlmSchV)	- Quantity threshold for operational area under § 1 para. 1
	- Sentence 1 :150000 kg
	- Sentence 2 :500000 kg

### 15.2 Chemical safety assessment

No additional information available.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Trade name: REF:	Bausch Arti-Spray <sup>®</sup> (colored blue, green, red) BK 286, BK 287, BK 288	
Product group: Version:	Occlusion sprays 005 / EN (English Translation of German SDS)	Revision date: 2024-05-29

# Section 16: Other information

### Indication of changes

Withdrawal of information on pentane and isobutane (due to formulation adjustment).

### Full text of H- and EUH-statements

Aerosol 1	Aerosol, Category 1.
Flam. Gas 1A	Flammable gases, Category 1A.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure: Compressed gas.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Aerosol 1 H222; H229 On the basis of test data. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Issued by:

Dr. Jean Bausch GmbH & Co. KG, Oskar-Schindler-Str.4, 50769 Köln, Tel.: +49-(0)221-70936-0, Fax: +49-(0)221-70936-66