SAFETY DATA SHEET

HALEON

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	CORSODYL 1% GEL
Registration number	-
Synonyms	CHLORHEXAMED PRAXIS 1% GEL * CHLORHEXAMED MOUTHGEL * CHLORHEXAMED MUNDGEL * CHLORHEXAMED GEL 1%, GEL * CORSODYL 10 MG/G, GEL DENTAIRE * CORSODYL 10 MG/G, GEL VOOR DENTAAL GEBRUIK * CORSODYL 10 MG/G, DENTALGEL * CORSODYL 1% W/W DENTAL GEL * CHLORHEXAMED 1% - GEL ZUR ANWENDUNG IN DER MUNDHÖHLE * CHLORHEXIDINE GLUCONATE 10MG/G OROMUCOSAL GEL MF1383 * MF1383 * CHLORHEXIDINE GLUCONATE, FORMULATED PRODUCT
Product code	MF1383
Issue date	13-May-2025
Version number	23
Revision date	13-May-2025
Supersedes date	06-December-2021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Oral Care
Uses advised against	No other uses are advised.

1.3. Details of the supplier of the safety data sheet

Company name	Haleon PLC
Address:	1st Floor, Building 5, The Heights Weybridge, Surrey KT13 0NY, United Kingdom
Telephone:	+44-20-8047-5000 (General Inquiries)
Email:	msds@haleon.com
Website:	www.haleon.com

EMERGENCY CONTACTS

	3E Global Incident Response
Telephone:	+(44) 20 35147487 or 0 800 680 0425 (In country) +(1) 760 476 3961 (International) 24/7; multi-language response
Contract Number:	335879

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards		
Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
Health hazards		
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Respiratory sensitisation	Category 1	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Environmental hazards		
Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:	CHLORHEXIDINE DIGLUCONATE

Hazard pictograms



Signal word Danger

Hazard statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P235	Keep cool.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting// equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapours.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/.
P284	Wear respiratory protection.

Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE/doctor/physician.
P370 + P378	In case of fire: Use foam, dry chemical powder or CO2 to extinguish.

Storage

P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information 3.5 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 3.5 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards See section 11 of the SDS for additional information on health hazards. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Isopropyl alcohol	3 - < 5	67-63-0 200-661-7	-	603-117-00-0	
Classification: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					
CHLORHEXIDINE DIGLUCONATE	1 - < 3	18472-51-0 242-354-0	-	-	
Classification: Skin Irrit. 2;H315, Eye Dam. 1;H318, Resp. Sens. 1;H334, STOT SE 3;H335, Aquatic Acute 1;H400, Aquatic Chronic 1;H410					
PEPPERMINT OIL, NATURAL	< 0.2	8006-90-4 -	-	-	
Classification: Skin Irrit. 2;H315, Skin Sens. 1;H317, Aquatic Chronic 2;H411					
Other components below reportable levels	90 - 100				

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.
M: M-factor
vPvB: very persistent and very bioaccumulative substance.
PBT: persistent, bioaccumulative and toxic substance.
#: This substance has been assigned Union workplace exposure limit(s).
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: call a poison centre or doctor / physician.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Alcohol resistant foam.

Unsuitable extinguishing media Water.

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures In case of fire and/or explosion do not breathe fumes.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
Storage class (TRGS 510): 3 (Flammable liquids)

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances
Hazard categories in accordance with Regulation (EC) No 1272/2008
- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tonnes; Upper-tier requirements = 200 tonnes)

7.3. Specific end use(s)

Oral Care Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Haleon Exposure Limits

Components	Type	Value	Form
CASTOR OIL, HYDROGENATED, ETHOXYLATED (CAS 61788-85-0)	OHC	1	>50 - </=500 ppm
CHLORHEXIDINE DIGLUCONATE (CAS 18472-51-0)	8 HR TWA	35 mcg/m3	RESPIRATORY SENSITISER, CORROSIVE
	OHC	3	RESPIRATORY SENSITISER, CORROSIVE
HYDROXYPROPYL METHYL CELLULOSE (CAS 9004-65-3)	OHC	1	

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

Components	Type	Value
Isopropyl alcohol (CAS 67-63-0)	STEL	1250 mg/m3
		500 ppm
	TWA	999 mg/m3
		400 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)	Not available.
Exposure guidelines	Occupational Exposure Limits are not relevant to the current physical form of the product.

8.2. Exposure controls

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Follow all local regulations if personal protective equipment (PPE) is used in the workplace.
Eye/face protection	Not normally needed. Chemical respirator with organic vapour cartridge and full facepiece. (e.g. EN 166).
Skin protection	
- Hand protection	Not normally needed. Select suitable chemical resistant protective gloves (EN 374) with a protective index 6 (>480min permeation time).
- Other	Not normally needed. (EN 14605 for splashes, EN ISO 13982 for dust). Wear suitable protective clothing.
Respiratory protection	No personal respiratory protective equipment normally required. Chemical respirator with organic vapour cartridge and full facepiece. Where breathable aerosols/dust are formed, use suitable combination filter for gases/vapours of organic, inorganic, acid inorganic, alkaline compounds and toxic particles (eg. EN 14387).
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. For advice on suitable monitoring methods, seek guidance from a qualified environment, health and safety professional.

Environmental exposure controls

Hazard guidance and control recommendations	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Gel.
Colour	Clear to opalescent.
Odour	Mint
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	56 °C (132.8 °F) Closed cup (Estimation based on components).
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.

Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information

Percent volatile	91.1 % estimated

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing.

11.1. Information on toxicological effects

Acute toxicity	Expected to be a low hazard for usual industrial or commercial handling by trained personnel. Not known.

Components	Species	Test Results
CHLORHEXIDINE DIGLUCONATE (CAS 18472-51-0)		
Acute		
Inhalation		
LC50	Rat	0.3 - 0.43 mg/l Chlorhexidine diacetate
Oral		
LD50	Rat	2000 mg/kg
Subchronic		
Dermal		
LOEL	Rabbit	250 mg/kg/day minimal irritation-chlorhexidine diacetate
NOAEL	Rabbit	500 mg/kg/day liver- chlorhexidine diacetate
Isopropyl alcohol (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	12.8 g/kg
Inhalation		
LC50	Rat	39 mg/l 8-hr
Oral		
LD50	Rat	5045 mg/kg
Subchronic		
Inhalation		
LOEL	Mouse	1500 ppm
	Rat	1500 ppm
NOEL	Mouse	500 ppm, 13 weeks
	Rat	500 ppm, 13 weeks

Components	Species	Test Results
PEPPERMINT OIL, NATURAL (CAS 8006-90-4)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Oral		
LD50	Rat	2426 mg/kg

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible.

Corrosivity

CHLORHEXIDINE DIGLUCONATE	OECD 404, Chlorhexidine diacetate Result: Negative Species: Rabbit

Irritation Corrosion - Skin

Isopropyl alcohol	Acute dermal irritation; OECD 404 Result: Non-irritant Notes: UN SIDS evaluation: 2-Propanol

Serious eye damage/eye irritation Causes serious eye irritation.

Eye

Isopropyl alcohol	OECD 405 Result: Mild irritant Species: Rabbit Notes: UN SIDS evaluation: 2-Propanol
CHLORHEXIDINE DIGLUCONATE	OECD 405, chlorhexidine diaceate Result: Severe Species: Rabbit

Respiratory sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation Due to partial or complete lack of data the classification is not possible.

Sensitisation

CHLORHEXIDINE DIGLUCONATE	Occupational exposure, Sensitive individuals Result: Positive Species: Human

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Mutagenicity

Isopropyl alcohol	Ames Result: Negative
CHLORHEXIDINE DIGLUCONATE	Ames, chlorhexidine digluconate Result: Negative Chromosomal Aberration Assay In Vitro, chlorhexidine digluconate Result: Negative Dominant lethal assay, chlorhexidine digluconate Result: Negative Species: Mouse in vivo cytogenetics assay, chlorhexidine digluconate Result: Negative Species: Hamster
Isopropyl alcohol	In vivo Micronucleus Result: Negative Species: Mouse mammalian cell mutation assay (CHO/HGPRT forward mutation assay) Result: Negative
CHLORHEXIDINE DIGLUCONATE	Micronucleus test, chlorhexidine digluconate Result: Negative Species: Mouse
Isopropyl alcohol	SA7 - Sister Chromatid Exchange Result: Negative Sister Chromatid Exchange, V79 cells Result: Negative

Carcinogenicity Carcinogenic effects are not expected as a result of occupational exposure.

Isopropyl alcohol	0, Inhalation study Result: Negative Species: Mouse Notes: UN SIDS evaluation: 2-Propanol 2 year bioassay, Inhalation study Result: Negative Species: Rat Notes: UN SIDS evaluation: 2-Propanol

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Reproductivity

Isopropyl alcohol	< 1200 mg/kg/day Embryo-foetal development, Developmental neurotoxicity Result: Foetal NOAEL Species: Rabbit Notes: UN SIDS evaluation: 2-Propanol < 240 mg/kg/day Epidemiology Result: Maternal NOAEL Species: Human < 400 mg/kg/day Embryo-foetal development Result: Maternal NOAEL Species: Rabbit Notes: UN SIDS evaluation: 2-Propanol < 480 mg/kg/day Epidemiology Result: Foetal NOAEL Species: Human < 500 mg/kg/day Two generation study Result: Maternal toxicity; adverse effects on offspring. Species: Rat Notes: UN SIDS evaluation: 2-Propanol
CHLORHEXIDINE DIGLUCONATE	15.63 mg/kg/day Embryofetal Development, Chlorhexidine diacetate Result: Maternal NOAEL Species: Rat 62.5 mg/kg/day Embryofetal Development, Chlorhexidine diacetate Result: Developmental NOAEL - High dose Species: Rat

Specific target organ toxicity - single exposure Due to partial or complete lack of data the classification is not possible.

Isopropyl alcohol	Result: Narcosis Organ: Central nervous system.

Specific target organ toxicity - repeated exposure Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance information No information available.

SECTION 12: Ecological information

12.1. Toxicity No data available for this product. Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.

Components		Species	Test Results
CHLORHEXIDINE DIGLUCONATE (CAS 18472-51-0)			
Aquatic			
Acute			
Fish	EC50	Brown trout (Adult Salmo trutta)	3.2 mg/l, 96 hours Static test
Isopropyl alcohol (CAS 67-63-0)			
Aquatic			
Acute			
Activated Sludge Respiration	IC50	Industrial sludge	> 1000 mg/l, 3 hours
Algae	EC50	Green algae (Scenedesmus subspicatus)	> 1000 mg/l, 72 hours
Crustacea	EC50	Water flea (Daphnia magna)	13299 mg/l, 48 hours Static test
Fish	EC50	Bluegill sunfish (Juvenile Lepomis macrochirus)	> 1400 mg/l, 96 hours Static test
		Fathead minnow (Juvenile Pimephales promelas)	> 6550 to < 10400 mg/l, 96 hours flow-through test
		Mosquito fish (Juvenile Gambusia affinis)	> 1400 mg/l, 96 hours Static test

12.2. Persistence and degradability No data is available on the degradability of this product.

Photolysis

Half-Life (Photolysis-Atmospheric)

Isopropyl alcohol	3.1 - 14.5 Days Measured

Biodegradability

Percent degradation (Aerobic biodegradation-inherent)

Isopropyl alcohol	99.9 %, 28 days Coupled Unit test (OECD 303A), Activated Sludge

Percent Degradation (Aerobic Biodegradation-Ready)

Isopropyl alcohol	95 %, 20 Days Batch activated sludge (BAS), Activated Sludge

12.3. Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol/water (log Kow)

Isopropyl alcohol	0.26

12.4. Mobility in soil No data available.

Mobility in general

Volatility

Henry's law

Isopropyl alcohol	0.000008 atm m^3/mol Measured, 25 °C

12.5. Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Isopropyl alcohol (CAS 67-63-0)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances
Hazard categories in accordance with Regulation (EC) No 1272/2008
- P5a, b or c FLAMMABLE LIQUIDS

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow the requirements of the Control of Substances Hazardous to Health Regulations 2002 [SI 2002/2677], as amended, when using this material.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
CAS: Chemical Abstract Service.
CEN: European Committee for Standardization.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MAC: Maximum Allowed Concentration.
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.
TLV: Threshold Limit Value.
TWA: Time Weighted Average.
VLE: Exposure Limit Value.
VME: Exposure Average Value.
vPvB: Very persistent and very bioaccumulative.

References

GSK Hazard Determination.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Revision information	This document has undergone significant changes and should be reviewed in its entirety.
Training information	Follow training instructions when handling this material.
Disclaimer	The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create any warranty, express or implied. It is the responsibility of the user to determine the applicability of this information and the suitability of the material or product for any particular purpose.