



Pony Testing International Group

Report No.: MQI0UABG2437617U3

MSDS Report

Sample Name
& Model

Li-ion battery 18500 3.7V 2000mAh 7.4Wh EM

Applicant

Guilin Woodpecker Medical Instrument Co.,Ltd

Address

Information Industrial Park, National High-Tech Zone,
Guilin, Guangxi, P.R.China 541004



No.: MQI0UABG2437617U3
Code: fJT113



北京实验室: (010) 83055000 新疆实验室: (0991) 6684186 贵州实验室: (0851) 85221000 合肥实验室: (0551) 63843474
北京谱尼科技公司: (010) 80415661 石家庄实验室: (0311) 85376660 上海实验室: (021) 64851999 深圳实验室: (0755) 26050909
北京谱尼计量实验室: (010) 82492998 西安实验室: (029) 89608785 苏州实验室: (0512) 62997900 深圳碰撞实验室: (0755) 26050909-846
青岛实验室: (0532) 88706866 西安创尼实验室: (029) 81123093 苏州汽车安全带及儿童安全座椅 谱尼深圳通测: (0755) 27673339
天津实验室: (022) 23607888 西安壹德威克实验室: (029) 62886819 碰撞实验室: (0512) 62997900 广州实验室: (020) 89224310
长春实验室: (0431) 80530198 呼和浩特实验室: (0471) 3450025 武汉车附所: (027) 82318175 南宁实验室: (0771) 5518818
大连实验室: (0411) 87336618 太原实验室: (0351) 7555722 武汉实验室: (027) 83997127 厦门实验室: (0592) 5568048
哈尔滨实验室: (0451) 58627755 成都实验室: (028) 87702708 杭州实验室: (0571) 87219096
郑州实验室: (0371) 69350670 成都谱尼计量实验室: (028) 87702708-8888 宁波实验室: (0574) 87977185

声明 Statement

1. 本证明/报告的结论仅对委托方所送样品负责。
The conclusion of the certificate/report is responsible for the provided sample only.
2. 委托方必须如实提供样品、申报和声明资料, 并保证与实际相符, 否则由委托方承担由此导致的全部后果和责任。
The applicant shall provide accurately and truly the description and statement of the sample, shall guarantee to match the sample and real situation which they provided and declared. Otherwise the application shall bear any relevant consequences and responsibility.
3. 如委托方提供的样品及相关资料存在虚假、伪造等情形, 所造成的全部后果和责任由委托方承担。
In case the sample and documents provided involved in the situation of fake and forgery, any consequences and responsibility caused by this shall be undertaken by applicant.
4. 本证明/报告私自转让、盗用、冒用、涂改、未经本单位批准的复制(全文复制除外)或以其它任何形式的篡改均属无效, 本单位将对上述行为严究其相应的法律责任。
The certificate/report is invalid in case of illegal transfer, embezzlement, imposture, modification or any altering, reproducing except in full, without approval of PONY. PONY shall investigate and affix the applicant's legal liability accordingly.
5. 本证明/报告不考虑国家及经营人差异。
The certificate/report takes no account of the differences of countries and applicants.
6. 本单位有权在完成证明/报告后处理委托方所送样品。
PONY has the right to dispose the provided sample after approval of the certificate/report.

▲ 防伪说明:

- (1) 报告编号是唯一的;
- (2) 报告采用特制防伪纸张印制, 纸张表面带有“PONY”防伪纹路, 该防伪纹路不支持复印, 即复制件不会带有“PONY”防伪纹路;
- (3) 报告采用的防伪纸张内部亦加带有高科技“PONY”防伪水印, 只有在验钞机等紫外线照射下方可显出无色荧光防伪字样。



全国服务热线
400-819-5688

WWW.PONYTEST.COM



集团微信订阅号



集团微信服务号

北京实验室: (010) 83055000	新疆实验室: (0991) 6684186	贵州实验室: (0851) 85221000	合肥实验室: (0551) 63843474
北京谱尼科技公司: (010) 80415661	石家庄实验室: (0311) 85376660	上海实验室: (021) 64851999	深圳实验室: (0755) 26050909
北京谱尼计量实验室: (010) 82492998	西安实验室: (029) 89608785	苏州实验室: (0512) 62997900	深圳谱尼计量实验室: (0755) 26050909-846
青岛实验室: (0532) 88706866	西安创尼实验室: (029) 81123093	苏州汽车安全带及儿童安全座椅	谱尼深圳通测: (0755) 27673339
天津实验室: (022) 23607888	西安壹德威克实验室: (029) 62886819	碰撞实验室: (0512) 62997900	广州实验室: (020) 89224310
长春实验室: (0431) 80530198	呼和浩特实验室: (0471) 3450025	武汉车附所: (027) 82318175	南宁实验室: (0771) 5518818
大连实验室: (0411) 87336618	太原实验室: (0351) 7555722	武汉实验室: (027) 83997127	厦门实验室: (0592) 5568048
哈尔滨实验室: (0451) 58627755	成都实验室: (028) 87702708	杭州实验室: (0571) 87219096	
郑州实验室: (0371) 69350670	成都谱尼计量实验室: (028) 87702708-8888	宁波实验室: (0574) 87977185	



PONY

Pony Testing International Group

Report No.: MQI0UABG2437617U3 Date: 2023-01-01 Page 1 of 10

Material Safety Data Sheet

Reference to ST/SG/AC.10/30/Rev.9 (GHS)

Section 1 - Chemical Product and Company Identification

Chemical Product Identification

Sample Name: Li-ion battery

Sample Model: 18500 3.7V 2000mAh 7.4Wh EM

Recommended Uses: Dental Medical Instrument

Restrictions on Use: N/A

Supplier Name: Shanghai PYTES Energy Co., Ltd

Address: No.3492 Jinqian Road, Fengxian District, Shanghai, China

Phone Number: 021-57475821

FAX: 021-57475827

E-mail: tracey_zhang@dlgbattery.cn

Emergency Phone Number: 021-57475821

Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

Classification according to GHS

Acute toxicity, oral (4)

Skin corrosion/irritation (2)

Serious eye damage/eye irritation (2A)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Label elements

Hazard pictogram(s):



Signal word:

Warning

Hazard statement(s):

H302 Harmful if swallowed

H315 Causes skin irritation

H319 Causes serious eye irritation

H335 May cause respiratory irritation

PONY 谱尼测试
Pony Testing International Group

Hotline 400-819-5688

www.ponytest.com

Pony Testing Group Shenzhen Co., Ltd.
Address: 3/F of Building 2, Building 1, Xinbaosheng Industrial Park, Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China
Phone: 0755-26050909

北京实验室: (010) 83055000 郑州实验室: (0371) 69350670 成都谱尼计量实验室: (028) 87702708 宁波实验室: (0574) 87736499
北京谱尼科技公司: (010) 80415661 郑州谱尼职业卫生公司: (0371) 80967099 贵州实验室: (0851) 85221000 合肥实验室: (0551) 63843474
北京谱尼计量实验室: (010) 82492998 新疆实验室: (0991) 6684186 上海实验室: (021) 64851999 深圳实验室: (0755) 26050909
青岛实验室: (0532) 88706866 石家庄实验室: (0311) 85376660 苏州实验室: (0512) 62997900 深圳谱尼计量实验室: (0755) 26050909-846
天津实验室: (022) 23607888 西安实验室: (029) 89608785 苏州汽车座椅实验室及儿童安全座椅 谱尼深圳通测: (0755) 27673339
长春实验室: (0431) 80530198 西安创亿检测科技有限公司: (029) 81123093 碰撞实验室: (0512) 62997900 广州实验室: (020) 89224310
沈阳实验室: (024) 22811886 西安壹博检测技术有限公司: (029) 85729073 武汉实验室: (027) 83997127 南宁实验室: (0771) 5518818
大连实验室: (0411) 87336618 呼和浩特实验室: (0471) 3450025 武汉车附所: (027) 82318175 厦门实验室: (0592) 5568048
哈尔滨实验室: (0451) 58627755 成都实验室: (028) 87702708 杭州实验室: (0571) 87219096



集团微信订阅号 集团微信服务号



Pony Testing International Group

Report No.: MQIUABG2437617U3 Date: 2023-01-01 Page 2 of 10

Precautionary statement(s):

Prevention:

- P264 Wash skin and clothing thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves, protective clothing, eye protection, face protection.
- P261 Avoid breathing dust, fume, gas, mist, vapours, spray.
- P271 Use only outdoors or in a well-ventilated area.

Response:

- P301 + P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.
- P330 Rinse mouth.
- P302 + P352 IF ON SKIN: Wash with plenty water.
- P321 Specific treatment (See additional emergency instructions).
- P333 + P313 If skin irritation or rash occurs: Get medical advice.
- P362 + P364 Take off contaminated clothing and wash it before reuse.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists: Get medical advice.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER, if you feel unwell.

Storage

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

Disposal:

- P501 Send contents to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

Section 3 – Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Cobalt lithium manganese nickel oxide	182442-95-1	695-690-9	30~45
Graphite	7782-42-5	231-955-3	15~25



Pony Testing International Group

Report No.: MQIUABG2437617U3 Date: 2023-01-01 Page 3 of 10

Polyvinylidene fluoride resin	24937-79-9	607-458-6	0.1~2
Copper	7440-50-8	231-159-6	5~10
Aluminium	7429-90-5	231-072-3	2~8
Carbon black	1333-86-4	215-609-9	0.5~2
Styrene-butadiene rubber 1500	9003-55-8	618-370-2	0.5~5
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	1~3

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Small Fire: Dry chemical, CO₂, water spray or regular foam. Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media:

No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture



Pony Testing International Group

Report No.: MQIUABG2437617U3 Date: 2023-01-01 Page 4 of 10

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature (>150°C (302°F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

Personal precautions:

As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate closed spaces before entering. Large Spill: Consider initial downwind evacuation for at least 100 meters (330 feet).

Protective equipment:

No data available.

Emergency procedures:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material. Leaking batteries and contaminated absorbent material should be placed in metal containers.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

For all waste handling must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.



Pony Testing International Group

Report No.: MQIUABG2437617U3 Date: 2023-01-01 Page 5 of 10

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
182442-95-1	N/A	N/A	N/A
7782-42-5	TLV-TWA 2mg/m ³	REL-TWA 2.5mg/m ³	PEL-TWA 15mppcf PEL-TWA 20mppcf
24937-79-9	N/A	N/A	N/A
7440-50-8	TLV-TWA 0.2mg/m ³ TLV-TWA 1mg/m ³	REL-TWA 1mg/m ³ REL-TWA 0.1mg/m ³	PEL-TWA 0.1mg/m ³ PEL-TWA 1mg/m ³
7429-90-5	TLV-TWA 1mg/m ³	REL-TWA 2mg/m ³ REL-TWA 5mg/m ³ REL-TWA 10mg/m ³	PEL-TWA 5mg/m ³ PEL-TWA 15mg/m ³
1333-86-4	TLV-TWA 3mg/m ³	REL-TWA 3.5mg/m ³	PEL-TWA 3.5mg/m ³
9003-55-8	N/A	N/A	N/A
21324-40-3	N/A	N/A	N/A

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment:**Respiratory protection:** Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.**Hand Protection:** Wear appropriate protective gloves to reduce skin contact.**Eye Protection:** Wear safety goggles or eye protection combined with respiratory protection.**Skin and Body Protection:** Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties



Pony Testing International Group

Report No.: MQIUABG2437617U3 Date: 2023-01-01 Page 6 of 10

Information on basic physical and chemical properties

Colour:	Blue.
Physical State:	Cylindrical.
Odour:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Boiling point or initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Flammability:	Not available.
Solubility:	Not available.
Lower and upper explosion limit/flammability limit:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
Kinematic viscosity:	Not available.
Partition coefficient: n-octanol/water (log value):	Not available.
Vapour pressure:	Not available.
Density and/or relative density:	Not available.
Relative vapour density:	Not available.
Particle characteristics:	Not available.
Other information:	
Voltage	3.7V
Electric capacity	2000mAh
Electric Energy	7.4Wh

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatible materials: Oxidizing agents, acid base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information



Pony Testing International Group

Report No.: MQIUABG2437617U3 Date: 2023-01-01 Page 7 of 10

Acute Toxicity:

CAS No.	LC50/LD50
182442-95-1	No data available.
7782-42-5	No data available.
24937-79-9	No data available.
7440-50-8	No data available.
7429-90-5	No data available.
1333-86-4	No data available.
9003-55-8	No data available.
21324-40-3	No data available.

Skin corrosion/irritation: No data available.**Serious eye damage/irritation:** No data available.**Respiratory or Skin sensitization:** No data available.**Germ Cell mutagenicity:** No data available.**Carcinogenicity:** No data available.**Reproductive toxicity:** No data available.**Specific target organ toxicity-Single exposure:** No data available.**Specific target organ toxicity-Repeated exposure:** No data available.**Aspiration hazard:** No data available.**Information on the likely routes of exposure:** No data available.**Eye:** No data available.**Skin:** No data available.**Ingestion:** No data available.**Inhalation:** No data available.

Section 12 - Ecological Information

Ecological Toxicity: No data available.**Persistence and degradability:** No data available.**Bioaccumulative Potential:** No data available.**Mobility in Soil:** No data available.**Other adverse effects:** No data available.



Pony Testing International Group

Report No.: MQIUABG2437617U3 Date: 2023-01-01 Page 8 of 10

Section 13 - Disposal Considerations

Disposal methods:

Recommendation:

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN or ID Number	
IATA	UN3481
IMDG	UN3481
Proper Shipping Name/Description	
IATA	Lithium ion batteries contained in equipment
IMDG	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT
Packing Group	
IATA	N/A
IMDG	N/A
Hazard Label	
IATA	N/A
IMDG	N/A
Environmental hazards	
Marine pollutant:	No
IMDG EmS:	F-A. S-I
Special precautions for user	No information available.

Transport information: The Li-ion battery 18500 3.7V 2000mAh 7.4Wh EM has passed the test UN38.3, according to the report ID: MPIAGIRL773897U5.

According to the Packing Instruction 967 section II of IATA DGR 64th Edition for transportation.

According to the special provision 188 of IMDG (40-20), the goods are not subject to other provision of this code.



Pony Testing International Group

Report No.: MQIUABG2437617U3 Date: 2023-01-01 Page 9 of 10

Note: Batteries weight in the package < 5kg. (By air, Batteries installed in equipment)

Transport Fashion: By air, by sea.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
182442-95-1	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed
24937-79-9	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
1333-86-4	Listed	Listed	Listed DSL	Listed
9003-55-8	Listed	Listed	Listed DSL	Listed
21324-40-3	Listed	Listed	Listed DSL	Listed

Section 16 - Other Information

Issue Date: 2023-01-01

Issue Department: Technical department

Modification record:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);



Report No.: MQI0UABG2437617U3 Date: 2023-01-01 Page 10 of 10

Pony Testing International Group

ACGIH: (American Conference of Governmental Industrial Hygienists);
 NIOSH: (US National Institute for Occupational Safety and Health);
 OSHA: (US Occupational Safety and Health);
 TLV: (Threshold Limit Value)
 TWA: (Time Weighted Average);
 STEL: (Short Term Exposure Limit);
 PEL: (Permissible Exposure Level);
 REL: (Recommended Exposure Limit);
 PC-STEEL: (Permissible concentration-short time exposure limit);
 PC-TWA: (Permissible concentration-time weighted average);
 IARC: (International Agency for Research on Cancer);
 LC50: (Lethal concentration, 50 percent kill);
 LD50: (Lethal dose, 50 percent kill);
 EC50: (Median effective concentration);
 BCF: (Bioconcentration Factor);
 BOD: (Biochemical oxygen demand);
 IECSC: (Inventory of Existing Chemical Substances in China);
 NOEC: (No observed effect concentration);
 NTP: (US National Toxicology Program);
 RTECS: (Registry of Toxic Effects of Chemical Substances);
 TOC: (Total Organic Carbon);
 TSCA: (Toxic Substances Control Act of USA);
 DSL: (the Domestic Substances List of Canada);
 NDSL: (the Non-domestic Substances List of Canada);
 IATA: (International Air Transport Association);
 IMDG: (International Maritime Dangerous Goods);
 TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations)

End of report