

# Okklusionsspray

11294-0016

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Okklusionsspray

Article number:

580-2007/-2008/-2009/-2010

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Occlusion spray.

Contact spray for dental use.

For professional users only

### 1.3. Details of the supplier of the safety data sheet

Company name: YETI Dentalprodukte GmbH

Street: Industriestrasse 3

Place: D-78234 Engen

Telephone: +49 7733-9410-0

Telefax: +49 7733-9410-22

Responsible Department: sdb@yeti-dental.com

Responsible for the safety data sheet: sds@gbk-ingelheim.de

### 1.4. Emergency telephone

+49 7733-9410-0 (Mo-Do 8:00 - 16:30, Fr 8:00 - 15:00)

number:

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

### 2.2. Label elements

#### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word:

Danger

Pictograms:



#### Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## Okklusionsspray

11294-0016

P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional advice on labelling

The product is labeled in accordance with Regulation (EC) no. 1272/2008 (GHS).

### 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture of organic solvents

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
106-97-8	Butane			50 - 100 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1; H220			
74-98-6	Propane			25 - 50 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			10 - 25 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
75-28-5	isobutane			2,5 - 10 %
	200-857-2	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately. Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours. In the event of symptoms refer for medical treatment.

#### After contact with skin

Wash off with soap and plenty of water. Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

#### After ingestion

Do not induce vomiting. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Summon a doctor immediately. Induce vomiting only upon the advice of a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause drowsiness or dizziness.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## Okklusionsspray

11294-0016

---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

##### **Unsuitable extinguishing media**

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Fire may produce: Carbon monoxide and carbon dioxide

#### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

##### **Additional information**

Heating will cause pressure rise with risk of bursting. Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Use only explosion-proof equipment. Ensure adequate ventilation. Use personal protective clothing. Keep away sources of ignition.

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

---

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### **Advice on safe handling**

Ensure adequate ventilation. Avoid contact with skin, eyes and clothing.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Do not spray on a naked flame or any other incandescent material.

Heating will cause pressure rise with risk of bursting.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### **Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

##### **Advice on storage compatibility**

Incompatible with oxidizing agents.

##### **Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

Occlusion spray.

Contact spray for dental use.

---

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

# Okklusionsspray

11294-0016

## Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

## 8.2. Exposure controls

### Protective and hygiene measures

Do not breathe spray Wash hands before breaks and immediately after handling the product . When using do not eat, drink or smoke. Take off immediately all contaminated clothing . Avoid contact with eyes, skin or mucous membrane.

### Eye/face protection

Safety goggles with side protection (EN 166).

### Hand protection

Protective gloves resistant to chemicals made off viton , minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

### Skin protection

Long sleeved clothing (EN 368).

### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol  
 Colour: transparent  
 Odour: characteristic  
 pH-Value: n.d.

### Changes in the physical state

Melting point: n.d.  
 Initial boiling point and boiling range: -11,7 °C  
 Sublimation point: n.d.  
 Softening point: n.d.  
 Pour point: n.d.  
 : n.d.  
 Flash point: n.d.  
 Explosive properties: Because of the high vapour pressure, containers are liable to burst if temperature rises.  
 Lower explosion limits: 1,5 vol. %  
 Upper explosion limits: 9,4 vol. %  
 Ignition temperature: 365 °C  
 n.d.  
 Vapour pressure: n.d.  
 Density (at 20 °C): 0,6 g/cm<sup>3</sup>  
 Bulk density: n.d.  
 Water solubility: (at 20 °C) insoluble  
 Partition coefficient: n.d.  
 Viscosity / dynamic: n.d.  
 Viscosity / kinematic: n.d.  
 Flow time: n.d.

## Okklussionspray

11294-0016

Vapour density: n.d.  
 Evaporation rate: n.d.  
 Solvent content: 95,60% (EU VOC)

### 9.2. Other information

Solid content: 4,4%

Other information  
 No data available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

### 10.4. Conditions to avoid

Fire or intense heat may cause violent rupture of packages.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicocinetics, metabolism and distribution

No toxicological data available.

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Method	Dose	Species	Source
106-97-8	Butane				
	inhalative (4 h) gas	LC50	658 ppm	Rat	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50	5050 mg/kg	Rat	
	dermal	LD50	12800 mg/kg	Rabbit	

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

#### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Practical experience

#### Other observations

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the

## Okklussionspray

11294-0016

product.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecological data are not available.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50	> 1000 mg/l	96 h		
	Acute crustacea toxicity	EC50	> 1000 mg/l	48 h		

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	Butane	2,89
75-28-5	isobutane	2,8

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Other adverse effects

No data available.

#### Further information

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

In accordance with regulations for special waste, must be taken to a special waste disposal. Should not be disposed of with household waste. Do not empty into drains

Keep in closed original container. Do not mix with other products.

##### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.

##### Contaminated packaging

Offer empty spray cans to an established disposal company.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
<b>14.4. Packing group:</b>	-
Hazard label:	2.1



Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L

# Okklussionspray

11294-0016

Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

## Inland waterways transport (ADN)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0

## Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

## Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg

## 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

## 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

## SECTION 15: Regulatory information

## Okklussionspray

11294-0016

---

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

---

### **SECTION 16: Other information**

#### **Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### **Relevant H and EUH statements (number and full text)**

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*