

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2018

Revision: 17.07.2018

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** UltraSeal XT® Hydro™
- **Article number:** 71109, 71110, 71111
- **Index number:** SDS 239-001.06
- **Relevant identified uses of the substance or mixture and uses advised against**
Professional Dental Pit and Fissure Sealant
- **Application of the substance / the mixture** Professional Dental Pit and Fissure Sealant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Ultradent Products Inc.
505 W. Ultradent Drive (10200 S)
South Jordan, UT 84095-3942
USA
onlineordersupport@ultradent.com
- **EC Responsible Person**
Ultradent Products GmbH
Am Westhoyer Berg 30
51149 Cologne Germany
Email: infoDe@ultradent.com
Emergency Phone: +49(0)2203-35-92-0
- **Further information obtainable from:** Customer Service
- **Emergency telephone number:**
CHEMTREC (NORTH AMERICA) : (800) 424-9300
(INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Triethylene Glycol Dimethacrylate
Diurethane Dimethacrylate
Organophosphine Oxide

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.07.2018

Revision: 17.07.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 1)

- **Hazard statements**

H317 May cause an allergic skin reaction.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 109-16-0	Triethylene Glycol Dimethacrylate	≤20%
EINECS: 203-652-6	⚠ Skin Sens. 1, H317	
CAS: 72869-86-4	Diurethane Dimethacrylate	< 10%
EINECS: 276-957-5	⚠ Skin Sens. 1, H317	
CAS: 1344-28-1	Aluminium Oxide	< 5%
EINECS: 215-691-6	substance with a Community workplace exposure limit	
CAS: 79-41-4	Methacrylic Acid	≤1%
EINECS: 201-204-4	⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1A, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312	
CAS: 162881-26-7	Organophosphine Oxide	< 1%
ELINCS: 423-340-5	⚠ Skin Sens. 1, H317; Aquatic Chronic 4, H413	
CAS: 10163-15-2	Sodium Monofluorophosphate	≤0.2%
EINECS: 233-433-0	⚠ Acute Tox. 4, H302	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**

- **After inhalation:**

Seek medical treatment in case of complaints.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.07.2018

Revision: 17.07.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Pick up mechanically.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** See product labelling.
- **Specific end use(s)** Professional Dental Pit and Fissure Sealant

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1344-28-1 Aluminium Oxide

WEL Long-term value: 10* 4** mg/m³
*inhalable dust **respirable dust

79-41-4 Methacrylic Acid

WEL Short-term value: 143 mg/m³, 40 ppm
Long-term value: 72 mg/m³, 20 ppm

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.07.2018

Revision: 17.07.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 3)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Not required.
- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - Form:** Liquid
 - Colour:** According to product specification
- **Odour:** Acrylic
- **Odour threshold:** Not determined.
- **pH-value:** Not applicable.
- **Change in condition**
 - Melting point/freezing point:** Undetermined.
 - Initial boiling point and boiling range:** Undetermined.
- **Flash point:** Not applicable.
- **Flammability (solid, gas):** Not determined.
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product does not present an explosion hazard.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.07.2018

Revision: 17.07.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 4)

· Vapour pressure:	Not applicable.
· Density at 20 °C:	1.67 g/cm ³
· Relative density	Not determined.
· Vapour density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Insoluble.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
VOC (EC)	0.00 %
· Solids content:	< 80 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
109-16-0 Triethylene Glycol Dimethacrylate		
Oral	LD50	>5,000 mg/kg (rat)
	LC50 Fish	16.4 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (mouse)
72869-86-4 Diurethane Dimethacrylate		
Oral	LD50	>5,000 mg/kg (rat)
1344-28-1 Aluminium Oxide		
Oral	LD50	>5,000 mg/kg (rat)
79-41-4 Methacrylic Acid		
Oral	LD50	1,250 mg/kg (mouse)
		1,060 mg/kg (rat)
		1,200 mg/kg (rabbit)
	LC50 Fish	86 mg/l (Fish)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.07.2018

Revision: 17.07.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 5)

Dermal	LD50	1,000 mg/kg (Guinea pig) 500 mg/kg (rabbit)
Inhalative	LC50/4 h	7.1 mg/l (rat)
162881-26-7 Organophosphine Oxide		
Oral	LD50	>2,000 mg/kg (rat)
	LC50 Fish	>0.09 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

· Aquatic toxicity:

109-16-0 Triethylene Glycol Dimethacrylate

Biodegradability	28 days (Aerobic) (Biodegradability testing)
Aqua toxicity	32 mg/l (daphnia) (No Observed Effect Concentration)
EC50	>100 mg/l (Algae) (Toxicity to algae)

72869-86-4 Diurethane Dimethacrylate

Biodegradability	28 days (Aerobic) (Biodegradability testing)
EC50	>0.6 mg/l (Algae) (Toxicity to algae) >1.2 mg/l (daphnia) (Toxicity to aquatic invertebrates)

79-41-4 Methacrylic Acid

EC50	<180 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
EC50	45 mg/l (Algae) (Toxicity to algae)

162881-26-7 Organophosphine Oxide

EC50 (static)	>1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
Aqua toxicity	≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test)
Toxicity to Aquatic Plants (static)	>0.26 mg/l (Plant) (Toxicity to algae)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.07.2018

Revision: 17.07.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 6)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

HP 13	Sensitising
-------	-------------

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|-----------------|
| · UN-Number | |
| · ADR, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · ADR, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · ADR, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · ADR, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Chemical safety assessment:**
Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.07.2018

Revision: 17.07.2018

Trade name: **UltraSeal XT® Hydro™**

(Contd. of page 7)

· **Relevant phrases**

H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H331 Toxic if inhaled.
 H413 May cause long lasting harmful effects to aquatic life.

· **Department issuing SDS:** Regulatory Affairs· **Contact:** Customer Service· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 3: Acute toxicity – Category 3
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Skin Sens. 1: Skin sensitisation – Category 1
 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

GB