

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758



desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : desmanol® pure

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Disinfectants and general biocidal products

Recommended restrictions
on use : For professional users only.

1.3 Details of the supplier of the safety data sheet

Producer : Schülke & Mayr GmbH
Robert-Koch-Str. 2

22851 Norderstedt
Germany
Telephone: +49 (0)40/ 52100-0
Telefax: +49 (0)40/ 52100318
mail@schuelke.com
www.schuelke.com

Supplier : Schülke & Mayr UK Ltd.
Cygnet House
1, Jenkin Road

Sheffield S9 1AT
United Kingdom
Telephone: +44 114 254 35 00
Telefax: +44 114 254 35 01
mail.uk@schulke.com

E-mail address of person
responsible for the
SDS/Contact person : Application Specialists
+49 (0)40/ 521 00 666
AD@schuelke.com

1.4 Emergency telephone number

Emergency telephone num-
ber : Carechem 24 International: +44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)**

Flammable liquids, Category 2

H225: Highly flammable liquid and vapour.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
propan-2-ol

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Vapours may form explosive mixtures with air.
Take precautionary measures against static discharges.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Alcoholic solution

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 70 - < 90
tetradecanol	112-72-1 204-000-3 --- 01-2119485910-33-XXXX	Eye Irrit. 2; H319 Aquatic Chronic 1; H410 M-Factor (Chronic aquatic toxicity): 1	>= 0.25 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Take off all contaminated clothing immediately.

If inhaled : Move to fresh air.
If symptoms persist, call a physician.

In case of skin contact : No hazards which require special first aid measures.

In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.

If swallowed : Prevent vomiting if possible.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

Aspiration hazard if swallowed - can enter lungs and cause damage.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.
Vapours are heavier than air and may spread along floors.
Vapour/air-mixtures are explosive at intense warming.
Pay attention to flashback.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus for firefighters

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapour.

6.2 Environmental precautions

Environmental precautions : Avoid subsoil penetration.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).

6.4 Reference to other sections

See chapter 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not spray on a naked flame or any incandescent material.
Keep away from sources of ignition - No smoking. Keep away
from children.

Advice on protection against : Take measures to prevent the build up of electrostatic charge.
fire and explosion Vapours may form explosive mixtures with air.

Hygiene measures : Keep away from food and drink.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Recommended storage temperature: 5 - 25°C
areas and containers

Further information on stor- : Keep container tightly closed. Keep away from direct sunlight.
age conditions Store at room temperature in the original container.

Advice on common storage : Do not store together with oxidising agents.
Do not store near acids.

7.3 Specific end use(s)

Specific use(s) : none

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m ³	GB EH40
		STEL	500 ppm 1,250 mg/m ³	GB EH40

Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
propan-2-ol	Workers	Skin contact	Long-term systemic effects	888 mg/kg
	Workers	Inhalation	Long-term systemic	500 mg/m ³

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

			effects	
tetradecanol	Workers	Skin contact	Long-term systemic effects	89 mg/kg
	Workers	Inhalation	Long-term local effects	178 mg/m3
	Workers	Inhalation	Long-term systemic effects	313 mg/m3

Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
propan-2-ol	Fresh water	140.9 mg/l
	Marine water	140.9 mg/l
	Fresh water sediment	552 mg/kg
	Marine sediment	552 mg/kg
	Soil	28 mg/kg
	Intermittent use/release	140.9 mg/l
	Effects on waste water treatment plants	2251 mg/l
tetradecanol	Oral	160 mg/kg food
	Fresh water	0.00063 mg/l
	Marine water	0.000063 mg/l
	Soil	0.428 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : If splashes are likely to occur, wear:
Safety glasses with side-shields conforming to EN166

Hand protection

Remarks : Not applicable

Respiratory protection : No personal respiratory protective equipment normally required.

Protective measures : Avoid contact with eyes.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : alcohol-like

Odour Threshold : not determined

pH : Not applicable

Melting point/freezing point : < -20 °C

Decomposition temperature : No data available

Boiling point/boiling range : 81 °C
Method: OECD Test Guideline 103

Flash point : 20 °C

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

Method: DIN EN ISO 13736

Evaporation rate	:	No data available
Flammability	:	Highly flammable liquid and vapour.
Upper explosion limit / Upper flammability limit	:	12 %(V) Raw material
Lower explosion limit / Lower flammability limit	:	2 %(V) Raw material
Vapour pressure	:	ca. 43 hPa (20 °C) Raw material
Relative vapour density	:	ca. 2.07 Raw material
Density	:	ca. 0.85 g/cm ³ (20 °C)
Solubility(ies)		
Water solubility	:	partly miscible (20 °C)
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	435 °C Method: Regulation (EC) No. 440/2008, Annex, A.15
Viscosity		
Viscosity, dynamic	:	ca. 3.6 mPa*s Method: ISO 3219
Viscosity, kinematic	:	not determined
Explosive properties	:	No data available
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Metal corrosion rate	:	Not corrosive to metals
Self-ignition	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapours may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

10.3 Possibility of hazardous reactions

Hazardous reactions : Exothermic reaction with strong acids.
Reaction with certain metals (e.g. iron)

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Exposure to sunlight.

10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents
Rubber products

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Components:

propan-2-ol:

Acute oral toxicity : LD50 (Rat): 5,840 mg/kg
Acute inhalation toxicity : LC50 (Rat): 39 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): 13,900 mg/kg
Method: OECD Test Guideline 402

tetradecanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Acute inhalation toxicity : Remarks: No data available
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Components:

propan-2-ol:

Result : No skin irritation

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758



desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

tetradecanol:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

propan-2-ol:

Result	: Eye irritation
--------	------------------

tetradecanol:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Components:

propan-2-ol:

Test Type	: Buehler Test
Species	: Guinea pig
Result	: Did not cause sensitisation on laboratory animals.

tetradecanol:

Test Type	: Maximisation Test
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Components:

propan-2-ol:

Genotoxicity in vitro	: Test Type: Ames test Method: Mutagenicity (Escherichia coli - reverse mutation assay) Result: Non mutagenic
Genotoxicity in vivo	: Species: Mouse

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

Method: Mutagenicity (micronucleus test)
Result: Non mutagenic

Germ cell mutagenicity- Assessment : Not mutagenic in Ames Test

tetradecanol:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Not mutagenic in Ames Test

Carcinogenicity

Based on available data, the classification criteria are not met.

Components:

propan-2-ol:

Remarks : Based on available data, the classification criteria are not met.

tetradecanol:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Components:

propan-2-ol:

Effects on foetal development : Species: Rat
Application Route: Oral
General Toxicity Maternal: NOAEL: 400 mg/kg body weight

Reproductive toxicity - Assessment : Based on available data, the classification criteria are not met.

tetradecanol:

Reproductive toxicity - Assessment : Based on available data, the classification criteria are not met.

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : May cause drowsiness or dizziness.

Components:

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

tetradecanol:

||Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Components:

propan-2-ol:

||Remarks : Based on available data, the classification criteria are not met.

tetradecanol:

||Remarks : Based on available data, the classification criteria are not met.

Repeated dose toxicity

Components:

propan-2-ol:

||Remarks : No data available

tetradecanol:

||Remarks : No data available

Aspiration toxicity

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks : There is no data available for this product.

SECTION 12: Ecological information

12.1 Toxicity

Components:

propan-2-ol:

||Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l
Exposure time: 96 h

||Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 10,000 mg/l
aquatic invertebrates Exposure time: 48 h

||Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
plants Exposure time: 72 h
Test Type: static test

EC50 (green algae): 1,800 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

Exposure time: 7 d

tetradecanol:

Toxicity to fish	: LC50 (Brachidanio rerio): > 100 mg/l Method: ISO 7346/2
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna): > 1 - 10 mg/l Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (Desmodesmus subspicatus (green algae)): 10 - 100 mg/l Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC: > 1 - 10 mg/l Species: Brachidanio rerio Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: > 0.001 - 0.01 mg/l Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211
M-Factor (Chronic aquatic toxicity)	: 1

12.2 Persistence and degradability

Product:

Biodegradability	: Result: Readily biodegradable, according to appropriate OECD test. Method: OECD Test Guideline 301D
------------------	--

Components:

propan-2-ol:

Biodegradability	: Result: Readily biodegradable.
------------------	----------------------------------

tetradecanol:

Biodegradability	: Result: Readily biodegradable.
------------------	----------------------------------

12.3 Bioaccumulative potential

Components:

propan-2-ol:

Bioaccumulation	: Remarks: No bioaccumulation is to be expected (log Pow <= 4).
Partition coefficient: n-octanol/water	: log Pow: 0.05 (20 °C) Method: OECD Test Guideline 107

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

tetradecanol:

Bioaccumulation : Remarks: Does not significantly accumulate in organisms.

12.4 Mobility in soil

Components:

propan-2-ol:

Mobility : Remarks: Mobile in soils

tetradecanol:

Mobility : Remarks: After release, adsorbs onto soil., The product evaporates slowly.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

Additional ecological information : No data is available on the product itself.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR : UN 1219

IMDG : UN 1219

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

IATA : UN 1219

14.2 UN proper shipping name

ADR : ISOPROPANOL

IMDG : ISOPROPANOL, SOLUTION

IATA : Isopropanol, solution

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable liquid

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable liquid

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758



desmanol® pure **No Change Service!**

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	: Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	: Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	: Not applicable

Volatile organic compounds	: Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 75 %	

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: Product contains substance(s) not listed on TSCA inventory.
AIIC	: All components are listed on the inventory, regulatory obligations/restrictions apply
DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
ISHL	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758

schülke 

desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

NZIoC	:	Not in compliance with the inventory
TECI	:	On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
H410	:	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended
by UK REACH Regulations SI 2019/758



desmanol® pure *No Change Service!*

Version
03.10

Revision Date:
16.01.2026

Date of last issue: 27.11.2023

Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN
- United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous
Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.