

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 4/23/2024 Revision date: 4/23/2024 Supersedes version of: 11/29/2023 Version: 7.00

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : smartwipes Wet / smartwipes wet&easy

Article number : REF 125220 smartwipes Wet neutral; REF 203458 smartwipes Wet lemon; REF 203459

smartwipes Wet ocean; REF 203460 smartwipes Wet tropic; REF 203461 smartwipes Wet bubble gum; REF 214375 smartwipes wet&easy; REF 219263 smartwipes Wet mango;

REF 219423 smartwipes Wet cocos

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Medical device

Germicide Cleaning agent

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier
Alfred Becht GmbH
Carl-Zeiss-Str. 16
P.O. Box 1145
77656 Offenburg

T +49 781 60586-0, F +49 781 60586-40

Email competent person

sds@kft.de

1.4. Emergency telephone number

Emergency number : Poison Information Center Freiburg

+ 49 761 19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226 Serious eye damage/eye irritation, Category 1 H318

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS05

Signal word (CLP) : Danger
Contains : n-propanol

Hazard statements (CLP) : H226 - Flammable liquid and vapour.
H318 - Causes serious eye damage.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P280 - Wear eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER, a doctor.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component		
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	n-propanol (71-23-8), butanone (78-93-3), Ethanol (64-17-5)	
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	n-propanol (71-23-8), butanone (78-93-3), Ethanol (64-17-5)	

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component		
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Ethanol (64-17-5), n-propanol (71-23-8), butanone (78-93-3)	

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Cleaning agent

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethanol substance with national workplace exposure limit(s) (DE)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	≥ 25 – < 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319
n-propanol	CAS-No.: 71-23-8 EC-No.: 200-746-9 EC Index-No.: 603-003-00-0	≥ 5 – < 10	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336
butanone substance with national workplace exposure limit(s) (DE); substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3	≥ 0.25 – < 1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Ethanol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	(50 ≤ C < 100) Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : When in doubt or if symptoms are observed, get medical advice. First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam.

Carbon dioxide.

Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : Explosive vapour/air mixtures may be formed.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide (CO2). Carbon monoxide.

5.3. Advice for firefighters

Firefighting instructions : Protect container with water spray.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

Other information : Do not allow run-off from fire fighting to enter drains or water courses. Cool closed

containers exposed to fire with water spray. Disposal must be done according to official

regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove all sources of ignition. Avoid contact with skin and eyes. Ensure adequate air

ventilation. Do not breathe gas/vapour/aerosol.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Avoid sub-soil penetration.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Cover spill with non combustible material, e.g.: sand/earth. Take up mechanically

(sweeping, shovelling) and collect in suitable container for disposal.

Other information Dispose of materials or solid residues at an authorized site. Disposal must be done

according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : In use, may form flammable vapour-air mixture.

Precautions for safe handling Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use only nonsparking tools. Use explosion-proof equipment. Wear personal protective equipment. Avoid

contact with skin and eyes.

Hygiene measures : Immediately remove contaminated or damp clothing. Do not eat, drink or smoke when using

this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Protect against frost. Store in a well-ventilated place. Keep cool. Keep container tightly

Heat and ignition sources Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Keep away from heat and direct sunlight.

Information about storage in one common storage Keep away from food, drink and animal feeding stuffs. Store away from Acids, oxidizing

materials.

facility

7.3. Specific end use(s)

Follow the directions!.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butanone (78-93-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Butanone
IOEL TWA	600 mg/m³
	200 ppm
IOEL STEL	900 mg/m³
	300 ppm

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butanone (78-93-3)		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Germany - Occupational Exposure Limits (TRGS 900)		
Local name	Butanon	
AGW (OEL TWA)	600 mg/m³	
	200 ppm	
Peak exposure limitation factor	1(I)	
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden	
Regulatory reference	TRGS900	
Germany - Biological limit values (TRGS 903)		
Local name	2-Butanon (Methylethylketon)	
Biological limit value	2 mg/l Parameter: 2-Butanon - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 05/2015 DFG	
Remark	U, b, 05/2015, DFG	
Regulatory reference	TRGS 903	
Ethanol (64-17-5)		
Germany - Occupational Exposure Limits (TRGS 90	0)	
Local name	Ethanol	
AGW (OEL TWA)	380 mg/m³	
	200 ppm	
Peak exposure limitation factor	4(II)	
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden	
Regulatory reference	TRGS900	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

n-propanol (71-23-8) DNEL/DMEL (Workers)	
DNEL/DMEL (General population) Acute - systemic effects, inhalation 518 mg/m³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butanone (78-93-3)		
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	900 mg/m³	
Long-term - systemic effects, dermal	1161 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	600 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, inhalation	450 mg/m³	
Long-term - systemic effects,oral	31 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	106 mg/m³	
Long-term - systemic effects, dermal	412 mg/kg bodyweight/day	
Ethanol (64-17-5)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	267 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	380 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects, inhalation	114 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.96 mg/l	
PNEC aqua (marine water)	0.79 mg/l	
PNEC aqua (intermittent, freshwater)	2.75 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3.6 mg/kg dwt	
PNEC sediment (marine water)	2.9 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.63 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	380 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	580 mg/l	
didecyldimethylammonium chloride (7173-51-5)		
PNEC (Water)		
PNEC aqua (freshwater)	0.0011 mg/l	
PNEC aqua (marine water)	0.00011 mg/l	
PNEC aqua (intermittent, freshwater)	0.00021 mg/l	
PNEC aqua (intermittent, marine water)	0.000021 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	61.86 mg/kg dwt	
PNEC sediment (marine water)	6.186 mg/kg dwt	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

didecyldimethylammonium chloride (7173-51-5) PNEC (Soil)	
PNEC (STP) PNEC sewage treatment plant 0.14 mg/l	

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Wear closed safety glasses. ISO 16321-1. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. EN 13034. EN ISO 13688

Hand protection:

In case of repeated or prolonged contact wear gloves. Chemically resistant protective gloves. Butyl rubber. Neoprene. Polyethylene. ISO 374-1. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. EN 143. Short term exposure. Breathing apparatus with filter. A-P2. Breathing equipment is only to be used in order to handle the residual risk of short term jobs if all other risk minimizing measures have been carried out e.g. retention and/or local exhaust. For details on conditions of use and maximum use concentrations, see DGUV Regulation 112-190 - Use of respiratory protective equipment.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product. Apply emollient cream.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid Colour : white.

Appearance : Inert medium impregnated with: Germicide.

Odour : alcohol odour.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available

Safety Data Sheet

Oxidising properties

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Boiling point : Not available Flammability : Not applicable

Explosive properties : Product is not explosive. Explosive vapour/air mixtures may be formed. Non oxidizing.

Lower explosion limit : Not applicable : Not applicable Upper explosion limit 25 °C Flash point Auto-ignition temperature Not applicable Decomposition temperature : Not available : < 10 (Solution) pH solution : Not available Viscosity, kinematic : Not applicable

Solubility : Water: Miscible (Solution)

Partition coefficient n-octanol/water (Log Kow) : Not available : Not applicable Partition coefficient n-octanol/water (Log Pow) Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : 0.91 g/cm³ (Solution) Relative density : Not available Relative vapour density at 20°C : Not applicable Particle size : Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Explosive vapour/air mixtures may be formed.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met) Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met) Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation	 Not classified (Based on available data, the classification criteria are not met) pH: < 10 (Solution)
Serious eye damage/irritation	Causes serious eye damage.pH: < 10 (Solution)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
n-propanol (71-23-8)	
STOT-single exposure	May cause drowsiness or dizziness.
butanone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

: Not classified (Not relevant)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Aspiration hazard

Hazardous to the aquatic environment, short–term

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term

: Not classified (Based on available data, the classification criteria are not met)

(chronic)

12.2. Persistence and degradability

smartwipes wet&easy		
Persistence and degradability	The product has not been tested.	
n-propanol (71-23-8)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	75 % (20 d)	
butanone (78-93-3)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	98 % (28 d; (OECD 301D method))	
Ethanol		
Biodegradation	84 % (20 d; Literature data)	

12.3. Bioaccumulative potential

nartwipes wet&easy	
Partition coefficient n-octanol/water (Log Pow)	Not applicable
Bioaccumulative potential	The product has not been tested.
propanol (71-23-8)	
Partition coefficient n-octanol/water (Log Pow)	0.2 (25 °C; pH 7; (OECD 117 method))

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

butanone (78-93-3)	
Partition coefficient n-octanol/water (Log Pow)	0.3 (40 °C; pH 7; (OECD 117 method))
Bioaccumulative potential	Bioaccumulation unlikely.
Ethanol Partition coefficient n-octanol/water (Log Pow) -0.35 (24 °C; pH 7,4; (OECD 107 method))	

12.4. Mobility in soil

smartwipes wet&easy	
Ecology - soil	The product has not been tested.
n-propanol (71-23-8)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.633 (Quantitative structure-activity relationship (QSAR))
Ethanol	
Surface tension	22.31 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 0.2 (Handbook and/or Scientific papers)

12.5. Results of PBT and vPvB assessment

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	n-propanol (71-23-8), butanone (78-93-3), Ethanol (64-17-5)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	n-propanol (71-23-8), butanone (78-93-3), Ethanol (64-17-5)

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : European waste catalogue. Disposal must be done according to official regulations.

Sewage disposal recommendations : Do not allow into drains or water courses.

Product/Packaging disposal recommendations : Do not dispose of with domestic waste.

Additional information : Flammable vapours may accumulate in the container.

European List of Waste (LoW, EC 2000/532) : 07 01 01* - aqueous washing liquids and mother liquors

4/23/2024 (Revision date) DE - en 10/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

- : HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID number					
UN 3175 UN 3175		UN 3175	UN 3175	UN 3175	
14.2. UN proper shippin	g name				
SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethanol; propan-1- ol) SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethanol; propan-2- ol)		Solids containing flammable liquid, n.o.s. (ethanol ; propan-2-ol)	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethanol ; propan-2- ol)	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethanol ; propan-2- ol)	
Transport document descr	iption				
UN 3175 SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethanol; propan-1- ol), 4.1, II, (E)	UN 3175 SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethanol; propan-2- ol), 4.1, II	UN 3175 Solids containing flammable liquid, n.o.s. (ethanol; propan-2-ol), 4.1, II	UN 3175 SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethanol ; propan-2- ol), 4.1, II	UN 3175 SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ethanol ; propan-2- ol), 4.1, II	
14.3. Transport hazard class(es)					
4.1	4.1	4.1	4.1	4.1	
14.4. Packing group					
II	II	II	II	II	
14.5. Environmental hazards					
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No	
No supplementary information	n available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 216, 274, 601

Limited quantities (ADR) : 1kg

4/23/2024 (Revision date) DE - en 11/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Excepted quantities (ADR) : E2
Transport category (ADR) : 2
Hazard identification number (Kemler No.) : 40

Orange plates :

40 3175

Tunnel restriction code (ADR) : E

Transport by sea

Special provisions (IMDG) : 216, 274
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-I

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y441
PCA limited quantity max net quantity (IATA) : 5kg
PCA packing instructions (IATA) : 445
PCA max net quantity (IATA) : 15kg
CAO max net quantity (IATA) : 50kg
Special provisions (IATA) : A46

Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 216, 274, 601, 800

Limited quantities (ADN) : 1 kg
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : B

Additional requirements/Remarks (ADN) : VE03, IN01 and IN02 apply only when this substance is carried in bulk or without packaging

Rail transport

Classification code (RID) : F1

Special provisions (RID) : 216, 274, 601

Limited quantities (RID): 1kgExcepted quantities (RID): E2Transport category (RID): 2Hazard identification number (RID): 40

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition

: Take note of Directive 94/33/EC on the protection of young people at work.

regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code Applicable on		
3(a) n-propanol ; butanone ; Ethanol		
3(b)	n-propanol ; butanone ; Ethanol	
40. smartwipes wet&easy ; n-propanol ; butanone ; Ethanol		

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I

15.1.2. National regulations

Germany

Employment restrictions

National Rules and Recommendations

- : Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.
- : TRGS 400: Risk Assessment for Activities involving Hazardous Substances.

TRGS 500: Protective measures.

TRGS 510: Storage of hazardous substances in non-stationary containers.

TRGS 520: Construction and operation of collection points and temporary storage for small

amounts of hazardous waste.

TRGS 900: Occupational Exposure Limits.

TRGS 903: Biological limit values.

Is subject to the 4th BImSchV (Federal Immission Control Ordinance) (Regulation on

Permitted Installations).

Water hazard class (WGK) Storage class (LGK, TRGS 510)

Hazardous Incident Ordinance (12. BlmSchV)

: WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

: LGK 4.1B - Flammable solids.

: Listed in the 12. BlmSchV (Annex I) under: 1.2.5.3

- Quantity threshold for operational area under § 1 para. 1

- Sentence 1 :5000000 kg

- Sentence 2:50000000 kg

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

4/23/2024 (Revision date) DE - en 13/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Indication of changes:

General revision.

Indication of changes	ndication of changes		
Section Changed item		Change	Comments
	General revision		
2	Classification	Modified	
2	Labelling	Modified	
9	Flash point	Added	

Abbreviations and acr	Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
BCF	Bioconcentration factor		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
EC50	Median effective concentration		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
PBT	Persistent Bioaccumulative Toxic		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
vPvB	Very Persistent and Very Bioaccumulative		
ATE	Acute Toxicity Estimate		
DNEL	Derived-No Effect Level		
DMEL	Derived Minimal Effect level		
IARC	International Agency for Research on Cancer		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
PNEC	Predicted No-Effect Concentration		
STP	Sewage treatment plant		
TLM	Median Tolerance Limit		

Data sources

[:] Information provided by the manufacturer. MSDSs of the suppliers. European Chemicals Agency, http://echa.europa.eu/.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Department issuing data specification sheet: : KFT Chemieservice GmbH

Im Leuschnerpark 3 D-64347 Griesheim

Phone: +49 6155-8981-400 Fax: +49 6155 8981-500 SDS Service: +49 6155 8981-522

Contact person : Dr. Maximilian Gatterdam

Full text of H- and EUF	text of H- and EUH-statements:	
EUH066	Repeated exposure may cause skin dryness or cracking.	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]		
Flam. Liq. 3	H226	
Eye Dam. 1	H318	Calculation method

KFT SDS EU 01 - Version 23.2

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.